

Lok-it!

HTI Short Arc Metal Halide lamps were designed as intense light sources primarily for moving head fixtures in the Entertainment marketplace.



Användningsområde

- Club & Disco
- Architecture & Architainment


Produktfördelar

- Higher luminous efficacy than conventional HID lamps provides higher fixture efficiency
- Snabbt lampbyte med bajonettfäste


Produktegenskaper

- Robust design with eXtreme Seal (XS) technology, allowing up to 450°C at the pinch seal
- Consistent lumen output over the life of the lamp





330962_Lok-it! HSD 300W80P28



330963_LOK-IT! HTI 1500 W60P50

Datablad produktfamilj

Tekniska data

Produktbeskrivning	Elektriska data		Fotometrisk data			Mått	
	Nominell märkspänning	Märkström	Nominell Ljusflöde	Färgtemperatur	Färgåtergivningsindex Ra	Diameter	Längd
Lok-it! HSD 300 W/80/P28	950 V		20500 lm	8700 K	>70	2300 mm	1223 mm
Lok-it! HTI 400 W/60/P28	490 V	62 A	30000 lm	6500 K	>80	2300 mm	1030 mm
Lok-it! HTI 700 W/60/P28	640 V	116 A	50000 lm	6000 K	>70	180 mm	1120 mm
Lok-it! HTI 700 W/75/P28	680 V	103 A	50000 lm	6700 K	>75	2300 mm	1120 mm
Lok-it! HTI 700 W/60/P50	600 V	1170 A	49000 lm	5800 K	75	250 mm	1250 mm
Lok-it! HTI 700 W/75/P50	100 V	103 A	50000 lm	7250 K	>75	250 mm	1250 mm
Lok-it! HTI 1500 W/60/P50	100 V	15 A	130000 lm	6000 K	>85	290 mm	1280 mm
Lok-it! HTI 1500 W/60/P50 M3W	100 V	15 A	130000 lm	6000 K		2900 mm	1300 mm
Lok-it! HTI 1600 W/60/P50	83.3 V	1920 A	140000 lm	6000 K	95	26.0 mm	125.0 mm
Lok-it! HTI 2000 W/75/P50	100 V	20 A	155000 lm	7500 K	77	2900 mm	1300 mm
Lok-it! HTI 2000 W/60/P50	107 V	186 A	165000 lm	6000 K	95	2900 mm	1300 mm

Produktbeskrivning	Avstånd a / LCL	Elektroдавstånd, kall	Livslängder	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
			Livslängd	Date of Declaration	Primary Article Identifier
Lok-it! HSD 300 W/80/P28	67,0 mm	5,0 mm	2000 h	05-03-2024	4008321493989 4008321644831
Lok-it! HTI 400 W/60/P28	56,0 mm	3,4 mm	750 h	05-03-2024	4008321605481
Lok-it! HTI 700 W/60/P28	56,0 mm	4.1 mm	750 h	16-02-2024	4052899179790
Lok-it! HTI 700 W/75/P28	56,0 mm	4,0 mm	750 h	22-02-2024	4008321510549
Lok-it! HTI 700 W/60/P50	65,0 mm	4.1 mm	750 h	29-02-2024	4062172398909
Lok-it! HTI 700 W/75/P50	65,0 mm	4,0 mm	750 h	05-03-2024	4008321485205
Lok-it! HTI 1500 W/60/P50	65,0 mm	6.1 mm	750 h	05-03-2024	4008321553416 4052899561823
Lok-it! HTI 1500 W/60/P50 M3W	67,0 mm	7,0 mm	750 h	06-03-2024	4008321818997
Lok-it! HTI 1600 W/60/P50			750 h	07-03-2024	4062172123488
Lok-it! HTI 2000 W/75/P50			750 h	07-03-2024	4062172133111
Lok-it! HTI 2000 W/60/P50			750 h	07-03-2024	4062172133098

Produktbeskrivning	Candidate List Substance 1	Declaration No. in SCIP database
Lok-it! HSD 300 W/80/P28	No declarable substances contained	No declarable substances contained
Lok-it! HTI 400 W/60/P28	No declarable substances contained	No declarable substances contained

Datablad produktfamilj

Produktbeskrivning	Candidate List Substance 1	Declaration No. in SCIP database
Lok-it! HTI 700 W/60/P28	No declarable substances contained	No declarable substances contained
Lok-it! HTI 700 W/75/P28	No declarable substances contained	No declarable substances contained
Lok-it! HTI 700 W/60/P50		In work
Lok-it! HTI 700 W/75/P50	No declarable substances contained	No declarable substances contained
Lok-it! HTI 1500 W/60/P50	No declarable substances contained	In work
Lok-it! HTI 1500 W/60/P50 M3W	No declarable substances contained	No declarable substances contained
Lok-it! HTI 1600 W/60/P50	No declarable substances contained	No declarable substances contained
Lok-it! HTI 2000 W/75/P50	No declarable substances contained	No declarable substances contained
Lok-it! HTI 2000 W/60/P50	No declarable substances contained	No declarable substances contained

Datablad produktfamilj

Säkerhetsanvisningar

På grund av deras kraftiga ljusstyrka, UV-strålning och höga interna tryck när de används får Lok-it!-lampor endast användas i slutna armaturer som är speciellt konstruerade för detta ändamål. Lämpliga filter måste säkerställa att UV-strålningen reduceras till en acceptabel nivå. Kvicksilver frigges om lampan går sönder. Speciella säkerhetsåtgärder måste vidtas. Ytterligare information finns tillgänglig på begäran eller kan hittas i broschyren som följde med lampan eller i bruksanvisningen.

Applikationsråd

För mer detaljerad applikationsinformation och grafik, vänligen se produktdatablad

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.