

Halogenlampor, strömstyrda PK30d-Sockel

Användningsområde

- Flygfältsbelysning




Produktfördelar

- Reducerade drift- och underhållskostnader tack vare den långa livslängden
- Omedelbar och oförändrad ljusstyrka under ljuskällans hela livslängden
- Flimmerfri funktion
- Kvicksilverfri

Produktegenskaper

- Dimbar
- På begäran tillgänglig med anslutningskombinationerna A, B, C/Z
- Infraröd strålning som ger ljus under sämsta möjliga förhållanden



Tekniska data

Produktbeskrivning	Produktinformation	Elektriska data			Fotometrisk data	Mått	
	Ordernummer	Nominell märkspänning	Lampspänning	Nominell watttal	Nominell Ljusflöde	Diameter	Längd
64319 Z/C 45-15	64319	120 V	66 A	4500 W	800 lm	135 mm	580 mm
64317 C 45-15	64317	6.8 V	6.6 A	45.00 W		13.5 mm	56.0 mm
64317 IRC-C 45-30	64317 IRC	682 V	66 A	4500 W		1500 mm	480 mm
64318 A 45-15	64318	68 V	66 A	4500 W		135 mm	500 mm
64319 IRC-A 45-30	64319 IRC	682 V	66 A	4500 W		1500 mm	480 mm
64328 HLX-A 65-15	64328 HLX	9.8 V	6.6 A	65.00 W		13.5 mm	48.0 mm
64328 HLX-Z/C 65-15	64328 HLX	9.8 V	6.6 A	65.00 W		13.5 mm	48.0 mm
64341 HLX-A 100-15	64341 HLX	120 V	6.6 A	100.00 W		13.5 mm	58.0 mm
64341 HLX-Z/C 100-15	64341 HLX	15.2 V	6.6 A	100.00 W		13.5 mm	48.0 mm
64342 HLX-C 100-15	64342 HLX	15.2 V	6.6 A	100.00 W		13.5 mm	56.0 mm
64361 HLX-A150-15	64361 HLX	22.7 V	6.6 A	150.00 W		13.5 mm	50.0 mm
64361 HLX-Z/C150-15	64361 HLX	22.7 V	6.6 A	150.00 W		13.5 mm	50.0 mm
64382 HLX-A 200-15	64382 HLX	30.3 V	6.6 A	200.00 W		13.5 mm	57.0 mm
64318 Z/C 45-15	64318	6.8 V	6.6 A	45.00 W		13.5 mm	50.0 mm
64319 A 45-15	64319	68 V	66 A	4500 W		135 mm	500 mm
64382 HLX-C 200-15	64382 HLX	30.3 V	6.6 A	200.00 W		13.5 mm	57.0 mm

Produktbeskrivning	Inbyggnadslängd	Längd med sockel utan sockelstift/ansl.	Avstånd a / LCL	Livslängder	Tillägg produktdata	Användningsområdet
				Livslängd	Sockel	Brinnläge
64319 Z/C 45-15	16,0 mm	32,00 mm	20,0 mm	1500 h	PK30d	s 90
64317 C 45-15	16,0 mm	36,00 mm	16,0 mm	1500 h	PK30d	s 90
64317 IRC-C 45-30	16,0 mm	28,00 mm	16,0 mm	3000 h	PK30d	s 90
64318 A 45-15	16,0 mm	30,00 mm	16,0 mm	1500 h	PK30d	s 90
64319 IRC-A 45-30	16,0 mm	32,00 mm	20,0 mm	3000 h	PK30d	s 90
64328 HLX-A 65-15	16,0 mm	36,00 mm	20,0 mm	1500 h	PK30d	s 90
64328 HLX-Z/C 65-15	16,0 mm	32,00 mm	20,0 mm	1500 h	PK30d	s 90
64341 HLX-A 100-15	16,0 mm	35,00 mm	20,0 mm	1500 h	PK30d	s 90
64341 HLX-Z/C 100-15	16,0 mm	35,00 mm	20,0 mm	1500 h	PK30d	s 90
64342 HLX-C 100-15	16,0 mm	40,00 mm	20,0 mm	1500 h	PK30d	s 90

Datablad produktfamilj

Produktbeskrivning	Inbyggnadslängd	Längd med sockel utan sockelstift/ansl.	Avstånd a / LCL	Livslängder	Tillägg produktdata	Användningsområdet
				Livslängd	Sockel	Brinnläge
64361 HLX-A150-15	16,0 mm	35,00 mm	20,0 mm	1500 h	PK30d	s 90
64361 HLX-Z/C150-15	16,0 mm	35,00 mm	20,0 mm	1500 h	PK30d	s 90
64382 HLX-A 200-15	16,0 mm	36,00 mm	20,0 mm	1500 h	PK30d	s 90 ¹⁾
64318 Z/C 45-15	16,0 mm	30,00 mm	16,0 mm	1500 h	PK30d	s 90
64319 A 45-15	16,0 mm	32,00 mm	20,0 mm	1500 h	PK30d	s 90
64382 HLX-C 200-15	16,0 mm	36,00 mm	20,0 mm	1500 h	PK30d	s 90

Environmental information
Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)

Produktbeskrivning	Date of Declaration	Primary Article Identifier	Candidate List Substance 1	CAS No. of substance 1
64319 Z/C 45-15	05-03-2024	4008321345578	Lead	7439-92-1
64317 C 45-15	05-03-2024	4008321345493	Lead	7439-92-1
64317 IRC-C 45-30	05-03-2024	4008321340139	Lead	7439-92-1
64318 A 45-15	05-03-2024	4008321345516	Lead	7439-92-1
64319 IRC-A 45-30	05-03-2024	4008321340153	Lead	7439-92-1
64328 HLX-A 65-15	06-05-2024	4008321345592	Lead	7439-92-1
64328 HLX-Z/C 65-15	06-05-2024	4008321345615	Lead	7439-92-1
64341 HLX-A 100-15	06-05-2024	4008321345639	Lead	7439-92-1
64341 HLX-Z/C 100-15	06-05-2024	4008321345653	Lead	7439-92-1
64342 HLX-C 100-15	06-05-2024	4008321345677	Lead	7439-92-1
64361 HLX-A150-15	06-05-2024	4008321345691	Lead	7439-92-1
64361 HLX-Z/C150-15	06-05-2024	4008321345714	Lead	7439-92-1
64382 HLX-A 200-15	06-05-2024	4008321345738	Lead	7439-92-1
64318 Z/C 45-15	05-03-2024	4008321345530	Lead	7439-92-1
64319 A 45-15	05-03-2024	4008321345554	Lead	7439-92-1
64382 HLX-C 200-15	06-05-2024	4008321345752	Lead	7439-92-1

Produktbeskrivning	Safe Use Instruction	Declaration No. in SCIP database	Landspecifika kategorier
			LIF
64319 Z/C 45-15	The identification of the Candidate List substance is sufficient to allow safe use of the article.	92d8f454-cc96-4495-94ef-e05e11f45f17	

Datablad produktfamilj

			Landspecifika kategorier
Produktbeskrivning	Safe Use Instruction	Declaration No. in SCIP database	LIF
64317 C 45-15	The identification of the Candidate List substance is sufficient to allow safe use of the article.	d9e66819-e040-4c44-bee8-4fcca5312c8c	J1/76
64317 IRC-C 45-30	The identification of the Candidate List substance is sufficient to allow safe use of the article.	5600ea4e-4016-4650-b994-3ad8acf8f5a0	J1/76
64318 A 45-15	The identification of the Candidate List substance is sufficient to allow safe use of the article.	ca26f0b4-6740-4bdb-a32d-7141568d2f95	J1/77
64319 IRC-A 45-30	The identification of the Candidate List substance is sufficient to allow safe use of the article.	0189083e-f10b-4e3a-9905-2b2db7d625df	
64328 HLX-A 65-15	The identification of the Candidate List substance is sufficient to allow safe use of the article.	7b45910a-859c-4e0f-92af-6a2767687bd8	
64328 HLX-Z/C 65-15	The identification of the Candidate List substance is sufficient to allow safe use of the article.	9ff014be-6b0f-4492-a2bc-1b13a5231d98	
64341 HLX-A 100-15	The identification of the Candidate List substance is sufficient to allow safe use of the article.	295ed5f7-e593-41fd-8379-aabc1761b8d4	J1/79
64341 HLX-Z/C 100-15	The identification of the Candidate List substance is sufficient to allow safe use of the article.	e7a8bc3b-5fc6-4418-aeba-14334908408b	J1/79

Datablad produktfamilj

			Landspecifika kategorier
Produktbeskrivning	Safe Use Instruction	Declaration No. in SCIP database	LIF
64342 HLX-C 100-15	The identification of the Candidate List substance is sufficient to allow safe use of the article.	df9336c6-f6aa-4cf0-a57f-d26ee6b412c0	J1/80
64361 HLX-A150-15	The identification of the Candidate List substance is sufficient to allow safe use of the article.	d0b74040-bc55-40f6-8ef2-40462d44a388	J1/83
64361 HLX-Z/C150-15	The identification of the Candidate List substance is sufficient to allow safe use of the article.	6c568582-5ec0-420c-8707-25bfc628d83c	J1/83
64382 HLX-A 200-15	The identification of the Candidate List substance is sufficient to allow safe use of the article.	bc021249-e7ad-4bcc-9af4-d2a7618c3637	J1/84
64318 Z/C 45-15	The identification of the Candidate List substance is sufficient to allow safe use of the article.	4a7f4d00-b3f6-4ff5-9dab-8b40cfc83462	J1/77
64319 A 45-15	The identification of the Candidate List substance is sufficient to allow safe use of the article.	b8092497-ad76-46a4-8f7f-7cd4786ab142	
64382 HLX-C 200-15	The identification of the Candidate List substance is sufficient to allow safe use of the article.	2af12407-76cf-479d-a022-f57985523da4	J1/84

1) Trots transversell glödtråd, kan lampan fritt placeras inom läge s 90

Datablad produktfamilj

Säkerhetsanvisningar

För att undvika personskador och materiella skador, får halogenlampor endast användas i passande armaturer som är försedda med lämpliga anordningar (skyddsskärmar, galler etc.) som säkerställer att inga delar/skärvor kan komma ut om lampan går sönder och att ingen ultraviolett strålning frigörs vid användningen. Det måste också finnas en varningsskylt som anger att lampan avger mycket värme. Detaljerad information finns tillgänglig på begäran.

Appliktionsråd

För mer detaljerad applikationsinformation och grafik, vänligen se produktdatablad

Referenser / Länkar

För ytterligare information om flygfältslampor, se broschyren:

"The reliable guiding stars - Effective solutions for airfield lighting: Tungsten halogen lamps and LED light sources".

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.