

XBO 7000W/DHP OFR

XBO DHP for digital cinema projection | Xenonlampor, kort ljusbåge



Användningsområde

- Cinema projection

Produktgenskaper

- Short arc with highest luminance for brighter screen illumination
- A lifetime of reliable performances with constant 6000 K color temperature
- Easy to maintain
- High level of arc stability
- Hot restart and instant light on screen
- Dimmable in a wide range



Tekniska data

Elektriska data

Märkström	170 A
Nominell watttal	700000 W
Strömstyrningsområde	130...175 A
Nominell märkspänning	410 V

Mått

Diameter	780 mm
Längd	4360 mm
Längd med sockel utan sockelstift/ansl.	393,00 mm
Kabellängd på ingångsidan	155 mm
Avstånd a / LCL	170,5 mm ¹⁾
Elektroдавstånd, kall	7,5 mm
produktvikt	102300 g
Kabellängd	1550

¹⁾ Avstånd från slutet av sockel till spets av elektrod (kallt)

Temperaturer och driftsförhållanden

Max omgivningstemperatur vid klämpunkt	230 °C
--	--------

Livslängder

Livslängd	400 h
Service Warranty Lifetime	500 h

Tillägg produktdata

Sockel, anod	SFaX30-9.5
Sockel, katod	SFa30-7.9

Användningsområden

Forcerad kylning	Forcerad
Brinnläge	s 15 p 15 ¹⁾

¹⁾ Vid vertikal drift, skall anoden (+) vara överst

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4062172031707

Produktdatablad

Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	885c4405-74b6-4820-817d-399a936e4918

Säkerhetsanvisningar

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4062172031707	XBO 7000W/DHP OFR	Transportförpacknin g 1	590 mm x 234 mm x 234 mm	32.31 dm ³	2149.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.