

## XBO 7000 W/HPN OFR

XBO HPN for digital cinema projection | Xenonlampor, kort ljusbåge




### Användningsområde

- Cinema projection

### Produkttegenskaper

- Short arc with highest luminance for brighter screen illumination
- A lifetime of reliable performances with constant 6000 K color temperature
- Easy to maintain
- High level of arc stability
- Hot restart and instant light on screen
- Dimmable in a wide range



## Tekniska data

### Elektriska data

Märkström	170 A
Nominell watttal	700000 W
Strömstyrningsområde	135...175 A
Nominell märkspänning	410 V

### Mått

Diameter	780 mm
Längd	4280 mm
Längd med sockel utan sockelstift/ansl.	389,00 mm
Avstånd a / LCL	171,5 mm <sup>1)</sup>
Kabellängd på ingångsidan	235 mm
Elektroдавstånd, kall	7,5 mm
produktvikt	102300 g
Kabellängd	2350

<sup>1)</sup> Avstånd från slutet av sockel till spets av elektrod (kallt)

### Temperaturer och driftsförhållanden

Max omgivningstemperatur vid klämpunkt	230 °C
--	--------

### Livslängder

Livslängd	400 h
Service Warranty Lifetime	500 h

### Tillägg produktdata

Socket, anod	SFaX30-9.5
Socket, katod	SFa30-20

### Användningsområden

Forcerad kylning	Forcerad
Brinnläge	s 15 p 15 <sup>1)</sup>

<sup>1)</sup> Vid vertikal drift, skall anoden (+) vara överst

### Environmental information

<b>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)</b>	
Date of Declaration	06-03-2024
Primary Article Identifier	4062172031691

## Produktdatablad

<b>Candidate List Substance 1</b>	Lead
<b>CAS No. of substance 1</b>	7439-92-1
<b>Safe Use Instruction</b>	The identification of the Candidate List substance is sufficient to allow safe use of the article.
<b>Declaration No. in SCIP database</b>	3028d909-e4c3-4ea0-8a8b-a58e460e8446

## Produktdatablad

### Säkerhetsanvisningar

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

### Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4062172031691	XBO 7000 W/HPN OFR	Transportförpackning g 1	590 mm x 234 mm x 234 mm	32.31 dm <sup>3</sup>	2164.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

### Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.