

XBO 4000W/HPN XL OFR

XBO HPN for digital cinema projection | Xenonlampor, kort ljusbåge



Användningsområde

- Cinema projection

Produktgenskaper

- Short arc with highest luminance for brighter screen illumination
- A lifetime of reliable performances with constant 6000 K color temperature
- Easy to maintain
- High level of arc stability
- Hot restart and instant light on screen
- Dimmable in a wide range



Tekniska data

Elektriska data

Märkström	122 A
Nominell watttal	400000 W
Strömstyrningsområde	92...132 A
Nominell märkspänning	330 V

Mått

Diameter	6000 mm
Längd	3450 mm
Längd med sockel utan sockelstift/ansl.	308,00 mm
Avstånd a / LCL	144,0 mm ¹⁾
Kabellängd på ingångsidan	235 mm
Elektroдавstånd, kall	6.1 mm
produktvikt	66400 g
Kabellängd	1950

¹⁾ Avstånd från slutet av sockel till spets av elektrod (kallt)

Temperaturer och driftsförhållanden

Max omgivningstemperatur vid klämpunkt	230 °C
--	--------

Livslängder

Service Warranty Lifetime	2100 h
---------------------------	--------

Tillägg produktdata

Sockel, anod	SFaX27-9.5
Sockel, katod	SFa27-20

Användningsområden

Forcerad kylning	Forcerad
Brinnläge	s 15 p 15 ¹⁾

¹⁾ Vid vertikal drift, skall anoden (+) vara överst

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	07-03-2024
Primary Article Identifier	4062172225489
Declaration No. in SCIP database	In work

Produktdatablad

Säkerhetsanvisningar

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4062172225489	XBO 4000W/HPN XL OFR	Transportförpackning g 1	500 mm x 204 mm x 204 mm	20.81 dm ³	1460.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.