

## HPL 93728 575 W 240 V

HPL | Högprestandalampor



### Produktfördelar

- Optimerad användning av genererat ljus i spotlighten



## Tekniska data

### Produktinformation

Ordernummer	93728 HPL 575W
-------------	----------------


### Elektriska data

Nominell märkspänning	240 V
Nominell watttal	575.00 W
On-mode power [AGGR]	645.00 W
Energy consumption in on-mode [AGGR]	645.0 kWh/1000h

### Fotometrisk data

Färgtemperatur	3200 K
Färgåtergivningsindex Ra	100
$\Phi_{use}$ value refers to luminous flux .. [AGGR]	360
Correlated color temperature CCT [AGGR]	3082 K
Useful luminous flux ( $\Phi_{use}$ ) [AGGR]	13280 lm
Chromaticity coordinate x [AGGR]	0.431
Chromaticity coordinate y [AGGR]	0.402

### Mått



Diameter	19.0 mm
Längd	104.0 mm
Längd med sockel utan sockelstift/ansl.	98,00 mm
Avstånd a / LCL	60,3 mm
Belyst område	9,5*11,5 mm <sup>2</sup> <sup>1)</sup>
Spiraldiameter	11,5 mm

<sup>1)</sup> Glödtråd av typ 6-C8

## Livslängder

Livslängd	400 h
-----------	-------

## Tillägg produktdata

Socket	G9.5 w/Hsink
Lighting technology used [AGGR]	HL

## Användningsområden

Brinnläge	Universal
-----------	-----------

## Certifikat och Standarder

Energy efficiency class [AGGR]	G
--------------------------------	---

## Landspecifika kategorier

Ordernummer	93728 HPL 575W
ANSI Kod	Other

## Logistikdata

EAN 10 of contained light source	4050300461830
----------------------------------	---------------

## Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	22-05-2024
Primary Article Identifier	4050300461830
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

## Produktdatablad

### Säkerhetsanvisningar

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (cover panel etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. Because of the heat produced only heat-resistant lamp connections (holders) may be used. Do not operate near people, or any materials that are flammable, sensitive to heat or affected by drying out. Detailed information is available on request.

### Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4050300461830	HPL 93728 575 W 240 V	Kapsel 1	40 mm x 40 mm x 129 mm	0.21 dm <sup>3</sup>	68.00 g
4050300461847	HPL 93728 575 W 240 V	Transportförpacknin g 12	176 mm x 149 mm x 135 mm	3.54 dm <sup>3</sup>	978.50 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

### Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.