

## HPL 93729 750 W 240 V

HPL | Högprestandalampor



### Produktfördelar

- Optimerad användning av genererat ljus i spotlighten



## Tekniska data

### Produktinformation

|             |            |
|-------------|------------|
| Ordernummer | 93729 750W |
|-------------|------------|


### Elektriska data

|                                      |                 |
|--------------------------------------|-----------------|
| Nominell märkspänning                | 240 V           |
| Nominell watttal                     | 750.00 W        |
| On-mode power [AGGR]                 | 810.00 W        |
| Energy consumption in on-mode [AGGR] | 810.0 kWh/1000h |

### Fotometrisk data

|  |          |
|--|----------|
| Färgtemperatur                                       | 3200 K   |
| Färgåtergivningsindex Ra                             | 100      |
| $\Phi_{use}$ value refers to luminous flux .. [AGGR] | 360      |
| Correlated color temperature CCT [AGGR]              | 3069 K   |
| Useful luminous flux ( $\Phi_{use}$ ) [AGGR]         | 16895 lm |
| Chromaticity coordinate x [AGGR]                     | 0.432    |
| Chromaticity coordinate y [AGGR]                     | 0.403    |

### Mått



|   |  |
|---|--|
| Diameter                                | 19.0 mm                                |
| Längd                                   | 104.0 mm                               |
| Längd med sockel utan sockelstift/ansl. | 104,00 mm                              |
| Avstånd a / LCL                         | 60,3 mm                                |
| Belyst område                           | 7,5*11,5 mm <sup>2</sup> <sup>1)</sup> |
| Spiraldiameter                          | 11,5 mm                                |

<sup>1)</sup> Glödtråd av typ 6-C8

## Produktdatablad

### Livslängder

|           |       |
|-----------|-------|
| Livslängd | 300 h |
|-----------|-------|

### Tillägg produktdata

|                                 |        |
|---------------------------------|--------|
| Socket                          | 2 pins |
| Lighting technology used [AGGR] | HL     |

### Användningsområden

|           |           |
|-----------|-----------|
| Brinnläge | Universal |
|-----------|-----------|

### Certifikat och Standarder

|                                |   |
|--------------------------------|---|
| Energy efficiency class [AGGR] | G |
|--------------------------------|---|

### Landspecifika kategorier

|             |            |
|-------------|------------|
| Ordernummer | 93729 750W |
| ANSI Kod    | Other      |

### Logistikdata

|                                  |               |
|----------------------------------|---------------|
| EAN 10 of contained light source | 4052899246898 |
|----------------------------------|---------------|

### Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                                    |
|---|------------------------------------|
| Date of Declaration   | 22-05-2024                         |
| Primary Article Identifier  | 4050300654225   4052899246898      |
| Candidate List Substance 1  | No declarable substances contained |
| Declaration No. in SCIP database                                      | No declarable substances contained |

## Produktdatablad

### Säkerhetsanvisningar

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (cover panel etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. Because of the heat produced only heat-resistant lamp connections (holders) may be used. Do not operate near people, or any materials that are flammable, sensitive to heat or affected by drying out. Detailed information is available on request.

### Logistiska data

| Produktnummer | Produktbeskrivning       | Förpackningsenhet (Styck/Enhet) | Dimensioner (längd x bredd x höjd) | Volym                | Bruttovikt |
|---------------|--------------------------|---------------------------------|------------------------------------|----------------------|------------|
| 4050300654225 | HPL 93729 750 W<br>240 V | Kapsel<br>1                     | - x - x -                          |                      |            |
| 4050300654232 | HPL 93729 750 W<br>240 V | Transportförpacknin<br>g<br>12  | 174 mm x 150 mm x<br>145 mm        | 3.78 dm <sup>3</sup> | 953.00 g   |

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

### Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.