

## HMI DIGITAL 2500 W

HMI DIGITAL | Metallhalogenlampor, ensidigt socklad



### Användningsområde

- Studio
- Stage
- TV

### Produktfördelar

- Suited for both analog and digital film production
- Robust stems, resulting in less breakage during transport
- Round moly-foil construction that evenly distributes heat and current extends for lamp longevity (6,000-18,000 W)
- Splash-proof carrying case is re-usable and allows lamps to be transported safely (6,000-18,000 W)

### Produktegenskaper

- High CRI of >90
- UV-Stop (UVS)
- Color temperature of 6,000 K (daylight)
- Extremely bright light of up to 100 lumens/watt
- Varm omstart möjlig



## Tekniska data

### Elektriska data

Nominell watttal	250000 W
Nominell märkspänning	118 V
Märkström	245 A

### Fotometrisk data

Nominell Ljusflöde	220000 lm
Färgtemperatur	6300 K
Färgåtergivningsindex Ra	90

### Mått

Diameter	6090 mm
Längd	2250 mm

### Livslängder

Livslängd	500 h
-----------	-------

### Tillägg produktdata

Socket	G38
--------	-----

### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4052899984295
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

## Produktdatablad

### Säkerhetsanvisningar

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

### Logistiska data

Produktnummer	Produktbeskrivning	Förpackningsenhet (Styck/Enhet)	Dimensioner (längd x bredd x höjd)	Volym	Bruttovikt
4052899984295	HMI DIGITAL 2500 W	Transportförpackning g 1	314 mm x 153 mm x 152 mm	7.30 dm <sup>3</sup>	539.00 g

Produktkoden gäller minsta tillåtna beställningskvantitet. En transportförpackning kan innehålla en eller flera produkter. Vid orderläggning, vänligen ange en eller flera transportförpackningar.

### Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.